

D300M

The QubePos D300M thermal receipt printer is a high-speed thermal receipt printer designed for repetitive tasks in limited operating time applications, especially for retail stores and fast-food applications. With the reliable printer module, it can print for prolonged durations while keeping the printing noise to a minimum. Along with a multi I/O interface, D300M is the best choice for high-quality demand solutions.



Paper Width 80mm



576 Dots Line



Speed 300mm/s



Front Paper Loading



Water Proof



Smoke-Proof



Printing - QR Code



Printing - 2D Barcode



D300M Specification

D300M

Printing

Printing Method	Direct Thermal
Paper Width	79.5±0.5mm 80mm
Print Width	72mm/ 76mm/ 80mm/ 64mm/ 48mm/ 52mm
Column Capacity	576 Dots/Line(Adjustable by Command)
Printing Speed	300 mm/s Max
Interface	USB+Serial+LAN
Line Spacing	3.75mm (Adjustable by Commands)
Column Number	80mm Paper : Font A - 42 Columns or 48 Columns/Font B - 56 Columns or 64 Columns/ Chinese, Traditional Chinese - 21 Columns or 24 Columns
Character Size	ANK, Font A: 1.5×3.0mm (12×24 dots) Font B: 1.1×2.1mm (9×17 dots) Chinese, Traditional Chinese: 3.0×3.0mm (24×24 dots)

Cutter

Auto Cutter	Partial
-------------	---------

Barcode Character

Extension Character Sheet	PC347 (Standard Europe), Katakana, PC850 (Multilingual), PC86 (Portuguese), PC863 (Canadian-French), PC865 (Nordic), West Europe, Greek, Hebrew, East Europe, Iran, WPC1252, PC866 (Cyrillic#2), PC852 (Latin2), PC858, IranII, Latvian, Arabic, PT151 (1251)
Barcode Types	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODE39/ITF/CODABAR/CODE93/CODE128
2D Barcode	QR Code / PDF417
Input Buffer	2048 Kbytes
NV Flash	256 Kbytes

Power

Power Adaptor	Input: AC110V/240V, 50~60Hz Output: DC 24V/2.5AV
Printer Input	DC 24V/2.5A
Cash Drawer	DC 24V/1A

Physical Characteristics

Weight	1.44KG
Dimensions (L x W x H)	144.5mm × 146mm × 188.5mm

Environmental Requirements

Operation Environment	Temperature : 0~45°C Humidity : RH 10~80%
Storage Environment	Temperature: -10~60°C Humidity: RH 10~90%

Reliability

Cutter Life	1.5 Million Cuts
Printer Head Life	150KM

Software

Emulation	ESC/POS
Driver	Windows/JPOS/Linux/Android/Mac/ OPOS
Utility	Windows & Linux Test Utility
SDK	iOS/Android/Windows

* The product pictures and display contents in the above pages are for illustration purpose only. The actual product effects (including but not limited to appearance, color, size) and screen display contents (including but not limited to background UI pictures) might differ.



Qube Apps Solution Sdn Bhd

No.2-30B, Jalan Desa 1/1, Desa Aman Puri, 52100 Kuala Lumpur, Wilayah Persekutuan.
Office No : +603-6262 5182 | Mobile No : +6010-8825182 | Reach Us at enquiry@qubeapps.com

