

HKCR EM4100

Card Prox-ID II comes with new firmware design and improved version of Card Prox series reader. It is designed to support most of the EM 4100 compliant series cards. This reader is an ideal solution for easy integration of card reader solutions into the desktop application environment.



USB Interface



10 Digits Card



Bright LED



Beeper Indication



Access Control



Attendance Control



Identification



Loyalty & Promotion



HKCR RM4100 Specification

HKCR EM4100

Technical Specifications

Connection Type	USB Interface
Power Source	From USB, Without Additional External Power Adaptor
Supported Card Format	Supported Most of The EM 4100 Compliant Series Cards
Frequency	125KHz
Output Format	10 Digit Card Number
Read Card Distance	Up to 5 -- 15cm (Depend on Card Quality)
Display	Read Indication LED and Beeper

Operation Condition

Operating Temperature	10 to 70 C
Humidity	40% to 80%

Physical Condition

Dimensions (L x W x H)	110.0mm x 80.0mm x 26.0mm
Weight	130g
Colour	Black

Device Driver Operating System Support

Driver	Driverless (No driver Installation Required)
O/S Platform	Window XP, Window Vista, Window Seven (7)

Typical Application

Application	<ul style="list-style-type: none">• Access Control• Attendance Control• Identification• Loyalty and Promotion
-------------	--

* The product pictures and display contents in the above pages are for illustration purpose only. The actual product effects (including but not limited to appearance, color, size) and screen display contents (including but not limited to background UI pictures) might differ.



Learn more at qubeapps.com

25-01, Level 25 iMazium, 8, Jalan SS 21/37, Damansara Utama, 47400 Petaling Jaya, Selangor.

Office No : +603-6262 5182 | Mobile No : +6010-8825182 | Reach Us at enquiry@qubeapps.com

